HYUNDA

L1030T













Features

10 Mega Pixel

3x optical Zoom

Slim camera with 3" Touchscreen

Smile Detection

Hot Keys

22 Program Modis

Image Stabilizer

Face Tracking

1920x1080 High Definition -Resolution

Metal Body







Specifications

Sensor	Туре
Lens	Focal Length
	Equivalent to 35mm Camera
	Digital Zoom
	Macro Mode
Display	
Shutter Speed	
ISO sensitivity	
Resolution	Movie
	Image
Storage	Internal memory
	External memory
Selftimer	
PictBridge (Direct Printing)	
File Format	
MP3	
Operating Environment	PC
	Mac
Interface	USB
	Other Interface
Power Source	
Dimensions (WxHxD)	
Weight	

35,5-106,5mm Capture Mode: 5x, Play Mode: 2-4x Wide: 6cm ~ 40cm 3" color Touchscreen LCD, (230.000 Pixels) 2 sec 1/1000 sec. Auto, 100, 200, 400, 800, 1600, 3200 640x480 AVI with audio (30 fps) - 16:9 Widescreen 3648x2736; 3264x2448; 2592x1944; 1920x1080 (HD); 640x480 32MB flash memory SD/SDHC (up to 8GB) 2 sec., 10 sec., double with LED indicator Compatible JPEG (EXIF 2.2, DCF 1.1, DPOF 1.1) No MS Windows 2000/ME/XP OS 9.0 or later USB 2.0 High-Speed Mic-in Lithium Ion Battery 92,5x55,9x18,5mm	10,34 Megapixel 1/2.3 " CCD
Capture Mode: 5x, Play Mode: 2-4x Wide: 6cm ~ 40cm 3" color Touchscreen LCD, (230.000 Pixels) 2 sec 1/1000 sec. Auto, 100, 200, 400, 800, 1600, 3200 640x480 AVI with audio (30 fps) - 16:9 Widescreen 3648x2736; 3264x2448; 2592x1944; 1920x1080 (HD); 640x480 32MB flash memory SD/SDHC (up to 8GB) 2 sec., 10 sec., double with LED indicator Compatible JPEG (EXIF 2.2, DCF 1.1, DPOF 1.1) No MS Windows 2000/ME/XP OS 9.0 or later USB 2.0 High-Speed Mic-in Lithium Ion Battery 92,5x55,9x18,5mm	Auto Focus 6.3 - 18.9mm / F3,1-5,6
Wide: 6cm ~ 40cm 3" color Touchscreen LCD, (230.000 Pixels) 2 sec 1/1000 sec. Auto, 100, 200, 400, 800, 1600, 3200 640x480 AVI with audio (30 fps) - 16:9 Widescreen 3648x2736; 3264x2448; 2592x1944; 1920x1080 (HD); 640x480 32MB flash memory SD/SDHC (up to 8GB) 2 sec., 10 sec., double with LED indicator Compatible JPEG (EXIF 2.2, DCF 1.1, DPOF 1.1) No MS Windows 2000/ME/XP OS 9.0 or later USB 2.0 High-Speed Mic-in Lithium lon Battery 92,5x55,9x18,5mm	35,5-106,5mm
3" color Touchscreen LCD, (230.000 Pixels) 2 sec 1/1000 sec. Auto, 100, 200, 400, 800, 1600, 3200 640x480 AVI with audio (30 fps) - 16:9 Widescreen 3648x2736; 3264x2448; 2592x1944; 1920x1080 (HD); 640x480 32MB flash memory SD/SDHC (up to 8GB) 2 sec., 10 sec., double with LED indicator Compatible JPEG (EXIF 2.2, DCF 1.1, DPOF 1.1) No MS Windows 2000/ME/XP OS 9.0 or later USB 2.0 High-Speed Mic-in Lithium Ion Battery 92,5x55,9x18,5mm	Capture Mode: 5x, Play Mode: 2-4x
2 sec 1/1000 sec. Auto, 100, 200, 400, 800, 1600, 3200 640x480 AVI with audio (30 fps) - 16:9 Widescreen 3648x2736; 3264x2448; 2592x1944; 1920x1080 (HD); 640x480 32MB flash memory SD/SDHC (up to 8GB) 2 sec., 10 sec., double with LED indicator Compatible JPEG (EXIF 2.2, DCF 1.1, DPOF 1.1) No MS Windows 2000/ME/XP OS 9.0 or later USB 2.0 High-Speed Mic-in Lithium Ion Battery 92,5x55,9x18,5mm	Wide: 6cm ~ 40cm
Auto, 100, 200, 400, 800, 1600, 3200 640x480 AVI with audio (30 fps) - 16:9 Widescreen 3648x2736; 3264x2448; 2592x1944; 1920x1080 (HD); 640x480 32MB flash memory SD/SDHC (up to 8GB) 2 sec., 10 sec., double with LED indicator Compatible JPEG (EXIF 2.2, DCF 1.1, DPOF 1.1) No MS Windows 2000/ME/XP OS 9.0 or later USB 2.0 High-Speed Mic-in Lithium Ion Battery 92,5x55,9x18,5mm	3" color Touchscreen LCD, (230.000 Pixels)
640x480 AVI with audio (30 fps) - 16:9 Widescreen 3648x2736; 3264x2448; 2592x1944; 1920x1080 (HD); 640x480 32MB flash memory SD/SDHC (up to 8GB) 2 sec., 10 sec., double with LED indicator Compatible JPEG (EXIF 2.2, DCF 1.1, DPOF 1.1) No MS Windows 2000/ME/XP OS 9.0 or later USB 2.0 High-Speed Mic-in Lithium Ion Battery 92,5x55,9x18,5mm	2 sec 1/1000 sec.
3648x2736; 3264x2448; 2592x1944; 1920x1080 (HD); 640x480 32MB flash memory SD/SDHC (up to 8GB) 2 sec., 10 sec., double with LED indicator Compatible JPEG (EXIF 2.2, DCF 1.1, DPOF 1.1) No MS Windows 2000/ME/XP OS 9.0 or later USB 2.0 High-Speed Mic-in Lithium Ion Battery 92,5x55,9x18,5mm	Auto, 100, 200, 400, 800, 1600, 3200
32MB flash memory SD/SDHC (up to 8GB) 2 sec., 10 sec., double with LED indicator Compatible JPEG (EXIF 2.2, DCF 1.1, DPOF 1.1) No MS Windows 2000/ME/XP OS 9.0 or later USB 2.0 High-Speed Mic-in Lithium Ion Battery 92,5x55,9x18,5mm	640x480 AVI with audio (30 fps) - 16:9 Widescreen
SD/SDHC (up to 8GB) 2 sec., 10 sec., double with LED indicator Compatible JPEG (EXIF 2.2, DCF 1.1, DPOF 1.1) No MS Windows 2000/ME/XP OS 9.0 or later USB 2.0 High-Speed Mic-in Lithium Ion Battery 92,5x55,9x18,5mm	3648x2736; 3264x2448; 2592x1944; 1920x1080 (HD); 640x480
2 sec., 10 sec., double with LED indicator Compatible JPEG (EXIF 2.2, DCF 1.1, DPOF 1.1) No MS Windows 2000/ME/XP OS 9.0 or later USB 2.0 High-Speed Mic-in Lithium Ion Battery 92,5x55,9x18,5mm	32MB flash memory
Compatible JPEG (EXIF 2.2, DCF 1.1, DPOF 1.1) No MS Windows 2000/ME/XP OS 9.0 or later USB 2.0 High-Speed Mic-in Lithium Ion Battery 92,5x55,9x18,5mm	SD/SDHC (up to 8GB)
JPEG (EXIF 2.2, DCF 1.1, DPOF 1.1) No MS Windows 2000/ME/XP OS 9.0 or later USB 2.0 High-Speed Mic-in Lithium Ion Battery 92,5x55,9x18,5mm	2 sec., 10 sec., double with LED indicator
No MS Windows 2000/ME/XP OS 9.0 or later USB 2.0 High-Speed Mic-in Lithium Ion Battery 92,5x55,9x18,5mm	Compatible
MS Windows 2000/ME/XP OS 9.0 or later USB 2.0 High-Speed Mic-in Lithium Ion Battery 92,5x55,9x18,5mm	JPEG (EXIF 2.2, DCF 1.1, DP0F 1.1)
OS 9.0 or later USB 2.0 High-Speed Mic-in Lithium Ion Battery 92,5x55,9x18,5mm	No
USB 2.0 High-Speed Mic-in Lithium Ion Battery 92,5x55,9x18,5mm	MS Windows 2000/ME/XP
Mic-in Lithium Ion Battery 92,5x55,9x18,5mm	OS 9.0 or later
Lithium Ion Battery 92,5x55,9x18,5mm	USB 2.0 High-Speed
92,5x55,9x18,5mm	Mic-in
	Lithium Ion Battery
Approx. 130g (without batteries and card)	92,5x55,9x18,5mm
	Approx. 130g (without batteries and card)



